



Flansch EN 1092-1 Typ 13 B PN 40

| DN | R-Gewinde | D | b | K | h1 | N2 | d1 | f | Anzahl | Gewinde | d3 | Gewicht |
|-----|-----------|-----|----|-----|----|-----|-----|---|--------|---------|----|---------|
| 10 | R 3/8" | 90 | 16 | 60 | 22 | 30 | 40 | 2 | 4 | M12 | 14 | 0,50 |
| 15 | R 1/2" | 95 | 16 | 65 | 22 | 35 | 45 | 2 | 4 | M12 | 14 | 0,50 |
| 20 | R 3/4" | 105 | 18 | 75 | 26 | 45 | 58 | 2 | 4 | M12 | 14 | 1,00 |
| 25 | R 1" | 115 | 18 | 85 | 28 | 52 | 68 | 2 | 4 | M12 | 14 | 1,00 |
| 32 | R 1 1/4" | 140 | 18 | 100 | 30 | 60 | 78 | 2 | 4 | M16 | 18 | 2,00 |
| 40 | R 1 1/2" | 150 | 18 | 110 | 32 | 70 | 88 | 2 | 4 | M16 | 18 | 2,00 |
| 50 | R 2" | 165 | 20 | 125 | 34 | 84 | 102 | 2 | 4 | M16 | 18 | 3,00 |
| 65 | R 2 1/2" | 185 | 22 | 145 | 38 | 104 | 122 | 2 | 8 | M16 | 18 | 4,00 |
| 80 | R 3" | 200 | 24 | 160 | 40 | 118 | 138 | 2 | 8 | M16 | 18 | 4,50 |
| 100 | R 4" | 235 | 24 | 190 | 44 | 145 | 162 | 2 | 8 | M20 | 22 | 6,50 |
| 125 | R 5" | 270 | 26 | 220 | 48 | 170 | 188 | 2 | 8 | M24 | 26 | 8,50 |
| 150 | R 6" | 300 | 28 | 250 | 52 | 200 | 218 | 2 | 8 | M24 | 26 | 11,00 |