



Flansch EN 1092-1 Typ 11 B1 PN 40

DN	d2	D	b	K	h1	S	h2	d1	f	Anzahl Gewinde	d3	Gewicht
10	17,2	90	16	60	35	1,8	6	40	2	4 M12	14	0,5
15	21,3	95	16	65	38	2,0	6	45	2	4 M12	14	1,0
20	26,9	105	18	75	40	2,3	6	58	2	4 M12	14	1,0
25	33,7	115	18	85	40	2,6	6	68	2	4 M12	14	1,0
32	42,4	140	18	100	42	2,6	6	78	2	4 M16	18	2,0
40	48,3	150	18	110	45	2,6	7	88	2	4 M16	18	2,0
50	60,3	165	20	125	48	2,9	8	102	2	4 M16	18	3,0
65	76,1	185	22	145	52	2,9	10	122	2	8 M16	18	4,0
80	88,9	200	24	160	58	3,2	12	138	2	8 M16	18	5,0
100	114,3	235	24	190	65	3,6	12	162	2	8 M20	22	6,5
125	139,7	270	26	220	68	4,0	12	188	2	8 M24	26	9,0
150	168,3	300	28	250	75	4,5	12	218	2	8 M24	26	11,5
200	219,1	375	34	320	88	6,3	16	285	2	12 M27	30	21,0
250	273	450	38	385	105	7,1	18	345	2	12 M30	33	34,0
300	323,9	515	42	450	115	8,0	18	410	2	16 M30	33	47,5
350	355,6	580	46	510	125	8,8	20	465	2	16 M33	36	69,0
400	406,4	660	50	585	135	11,0	20	535	2	16 M36	39	98,0
450	457	685	57	610	135	12,5	20	560	2	20 M36	39	105,0
500	508	755	57	670	140	14,2	20	615	2	20 M39	42	130,5
600	610	890	72	795	150	16,0	20	735	2	20 M45	48	211,5